


25/100L 25/50L



扁鋼中心間距為25mm 壓鎖鋼格板 常用規格及荷載表  
FLAT BAR CENTERS 25mm PRESSURE-LOCKED GRATING SAFE LOADS AND DEFLECTIONS

型號 TYPE	扁鋼 寬度 DEPTH mm	扁鋼 厚度 THICK mm	橫杆尺寸 CROSS BAR SIZE mm	理論重量 MASS kg/m <sup>2</sup>	跨距 SPAN mm															
					200	400	600	800	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	
G603/25/50L	60	3	20X2	72.4	U	2203	550	244	137	88	61	44	34	27	22	18	15	13	11	9
					D	0.11	0.46	1.03	1.83	2.88	4.16	5.58	7.39	9.45	11.80	14.23	16.91	20.32	23.34	25.48
G603/25/100L	60	3	20X2	69.0	C	220	110	73	55	44	36	31	27	24	22	20	18	16	15	14
					D	0.09	0.37	0.82	1.47	2.31	3.28	4.51	5.90	7.51	9.51	11.59	13.67	15.63	18.48	21.45
G602/25/50L	60	2	20X2	51.5	U	1468	367	163	91	58	40	29	22	18	14	12	10	8	7	
					D	0.11	0.46	1.03	1.83	2.85	4.09	5.52	7.18	9.46	11.29	14.25	16.95	18.88	22.40	
G602/25/100L	60	2	20X2	48.2	C	146	73	48	36	29	24	20	18	16	14	13	12	11	10	
					D	0.09	0.37	0.81	1.45	2.29	3.28	4.37	5.90	7.52	9.11	11.34	13.71	16.14	18.55	
G503/25/50L	50	3	20X2	61.5	U	1530	382	170	95	61	42	31	23	18	15	12	10	9		
					D	0.14	0.55	1.24	2.20	3.46	4.96	6.81	8.68	10.95	14.00	16.54	19.70	24.57		
G503/25/100L	50	3	20X2	58.1	C	153	76	51	38	30	25	21	19	17	15	13	12	11		
					D	0.11	0.44	0.99	1.76	2.73	3.95	5.30	7.21	9.25	11.30	13.19	15.97	18.84		
G502/25/50L	50	2	20X2	44.1	U	1020	255	113	63	40	28	20	15	12	10	8	7			
					D	0.14	0.55	1.24	2.19	3.40	4.96	6.60	8.51	10.97	14.02	16.58	20.69			
G502/25/100L	50	2	20X2	40.7	C	102	51	34	25	20	17	14	12	11	10	9	8			
					D	0.11	0.44	0.99	1.74	2.73	4.03	5.31	6.85	9.00	11.33	13.71	16.03			
G453/25/50L	45	3	10X2	52.6	U	1239	309	137	77	49	34	25	19	16	13	10	8			
					D	0.15	0.61	1.37	2.45	3.81	5.51	7.55	9.85	12.54	15.81	18.96	21.73			
G453/25/100L	45	3	10X2	50.9	C	123	61	41	30	24	20	17	15	12	12	11	10			
					D	0.12	0.46	1.10	1.91	3.00	4.34	5.90	7.83	9.03	12.45	15.34	18.32			
G452/25/50L	45	2	10X2	37.0	U	826	206	91	51	33	22	16	12	10	8	6				
					D	0.15	0.61	1.37	2.43	3.66	5.36	7.26	9.35	12.56	15.44	17.19				
G452/25/100L	45	2	10X2	35.3	C	82	41	27	20	16	13	11	10	9	8	7				
					D	0.12	0.49	1.08	1.91	3.00	4.24	5.74	7.84	10.13	12.48	14.72				
G403/25/50L	40	3	10X2	47.1	U	979	244	108	61	39	27	19	15	12	9	8				
					D	0.17	0.69	1.54	2.76	4.33	6.25	8.20	11.11	14.34	16.58	21.71				
G403/25/100L	40	3	10X2	45.4	C	97	48	32	24	19	16	13	12	10	9	8				
					D	0.14	0.54	1.22	2.18	3.38	4.96	6.45	8.95	10.75	13.42	16.10				
G402/25/50L	40	2	10X2	33.2	U	652	163	72	40	26	18	13	10	8	6	5				
					D	0.17	0.69	1.54	2.72	4.33	6.25	8.42	11.12	14.36	16.62	20.47				
G402/25/100L	40	2	10X2	31.5	C	65	32	21	16	13	10	9	8	7	6	5				
					D	0.14	0.54	1.20	2.18	3.47	4.66	6.70	8.96	11.29	13.45	15.21				
G353/25/50L	35	3	10X2	41.7	U	749	187	83	46	29	20	15	11	9	7	6				
					D	0.20	0.79	1.77	3.11	4.81	6.93	9.69	12.23	16.15	19.37	24.53				
G353/25/100L	35	3	10X2	40.0	C	74	37	24	18	14	12	10	9	8	7	6				
					D	0.16	0.62	1.37	2.44	3.73	5.57	7.44	10.08	12.90	15.70	18.25				
G352/25/50L	35	2	10X2	29.5	U	499	124	55	31	19	13	10	7	6	5					
					D	0.20	0.78	1.76	3.15	4.74	6.76	9.70	11.71	16.18	20.72					
G352/25/100L	35	2	10X2	27.8	C	49	24	16	12	10	8	7	6	5	5					
					D	0.15	0.61	1.37	2.44	4.00	5.57	7.81	10.10	12.17	16.79					
G303/25/50L	30	3	10X2	36.2	U	550	137	61	34	22	15	11	8	6	5					
					D	0.23	0.91	2.07	3.66	5.81	8.27	11.33	14.21	17.31	22.22					
G303/25/100L	30	3	10X2	34.5	C	55	27	18	13	11	9	7	6	6	5					
					D	0.18	0.72	1.63	2.81	4.67	6.65	8.33	10.80	15.49	18.05					
G302/25/50L	30	2	10X2	25.8	U	367	91	40	22	14	10	7	5	4						
					D	0.23	0.91	2.03	3.55	5.55	8.28	10.85	13.39	17.35						
G302/25/100L	30	2	10X2	24.1	C	36	18	12	9	7	6	5	4	4						
					D	0.18	0.72	1.63	2.91	4.46	6.66	8.92	10.83	15.53						
G253/25/50L	25	3	10X2	30.7	U	382	95	42	23	15	10	7	5	4						
					D	0.27	1.10	2.46	4.29	6.87	9.59	12.58	15.57	20.21						
G253/25/100L	25	3	10X2	29.0	C	38	19	12	9	7	6	5	4	4						
					D	0.22	0.88	1.88	3.37	5.16	7.72	10.36	12.62	18.12						
G252/25/50L	25	2	10X2	22.0	U	255	63	28	15	10	7	5	3							
					D	0.28	1.09	2.46	4.20	6.88	10.06	13.47	14.13							
G252/25/100L	25	2	10X2	20.3	C	25	12	8	6	5	4	3	3							
					D	0.22	0.83	1.88	3.37	5.53	7.73	9.40	14.13							
G203/25/50L	20	3	10X2	25.3	U	244	61	27	15	9	6	5	3							
					D	0.34	1.38	3.10	5.48	8.10	11.34	17.64	18.59							
G203/25/100L	20	3	10X2	23.6	C	24	12	8	6	4	4	3	3							
					D	0.27	1.08	2.45	4.40	5.82	10.13	12.34	18.59							
G202/25/50L	20	2	10X2	18.3	U	163	40	18	10	6	4	3								
					D	0.34	1.35	3.10	5.48	8.12	11.37	16.00								
G202/25/100L	20	2	10X2	16.6	C	16	8	5	4	3	2	2								
					D	0.27	1.08	2.30	4.40	6.54	7.73	12.39								

U-格棚板安全承載許可的最大均布荷載，  
Safe uniform load, kN/m<sup>2</sup>;  
C-格棚板安全承載許可的最大線荷載，  
Safe concentrated load, kN/m;  
D-格棚板在所列荷載作用下的最大撓度，  
Max. deflection, mm;  
綠色粗線左方區域的格棚板在 2kN/m<sup>2</sup> 的  
均布荷載作用下其最大撓度小於 4 mm。  
The left side of the green bold line in this  
table, those gratings not exceeds 4 mm  
deflection for uniform load of 2kN/m<sup>2</sup>.